

HOMOGENEOUS  
COMPACT VINYL

## Centra 43

CERTIFICATION & CLASSIFICATION	STANDARDS	Centra 43
<b>Classification</b>	ISO 10874 – EN 685	Commercial: 34 Industrial: 43
<b>Type of floor covering</b>	ISO 10581 – EN 649	Homogeneous vinyl flooring. Single layered. Type I.
<b>ISO certification</b>		Jaslo ISO 9001, Jaslo ISO 14001
TECHNICAL CHARACTERISTICS	STANDARDS	Centra 43
<b>Total thickness</b>	ISO 24346 – EN 428	2.0 mm
<b>Wear layer thickness</b>	ISO 24340 – EN 429	2.0 mm
<b>Total weight/m<sup>2</sup></b>	ISO 23997 – EN 430	3000 g
<b>PUR</b>		Yes
TECHNICAL PERFORMANCES	STANDARDS	Centra 43
<b>Residual indentation</b>	ISO 24343-1 – EN 433	Requirement $\leq 0.1$ mm
<b>Reaction to fire</b>	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>f1</sub> s1 $\geq 8$ kW/m <sup>2</sup> Pass
<b>Dimensional stability</b>	ISO 23999 – EN 434	$\leq 0.40$ % for rolls $\leq 0.25$ % for tiles
<b>Castor chair test</b>	ISO 4918 – EN 425	Suitable
<b>Static electrical charge</b>	EN 1815	$\leq 2$ kV
<b>Electrical resistance</b>	EN 1081	$\leq 10^9 \Omega$
<b>Light fastness</b>	EN ISO 105-B02	$\geq$ level 6
<b>Chemical resistance</b>	ISO 26987 – EN 423	Good resistance
<b>Bacteria resistance</b>	ISO 846: Part C	Does not favour growth
<b>Clean room test</b>	ASTM F24-04 ASTM F51-00	Class A
<b>Slip resistance</b>	DIN 51130 EN 13893	R9 $\geq 0.3$
<b>Underfloor heating</b>		Suitable – max 27°C
<b>Form of delivery</b>	ISO 24341 – EN 426 Sheet (rolls)	Approx. 20 running metres x 200 cm
	ISO 24342 – EN 427 Tiles (box)	61.0 x 61.0* cm – 14 tiles/box = 5.21 m <sup>2</sup> 50.0 x 50.0* cm – 24 tiles/box = 6 m <sup>2</sup>
<b>Colours</b>		18

\* Available for orders for at least 700 m<sup>2</sup>

The above information is subject to modification for the benefit of further improvement (03/2015).