

Starfloor Click 20

Technical data sheet
05-2017

Class of Use	EN ISO 10874: 2013	22 
--------------	--------------------	--

PRODUCT ID

Material group		36003
Dimensions	ISO 24342	18,3 x 122 cm = 12/box = 2,68 m ²
Locking system		Lift-2-Lock®
Commercial warranty		10 years residential use

TECHNICAL CHARACTERISTICS

Total thickness	EN ISO 24346	3,2 mm
Wear layer thickness	EN ISO 24340	0,20 mm
Wear layer binder content	ISO 10582	Type I
Dimension - Length	EN ISO 24342	122 cm
Dimension - Width	EN ISO 24342	18,3 cm
Surface Treatment (PUR)		Supreme
Bevelled edges		Microbevels
Total weight	ISO 29997-EN430	6,8 kg/m ²

TECHNICAL PERFORMANCES

Dimensional stability	EN ISO 23999	≤ 0,10 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	EN 13501-1	B _f -s1
Residual indentation	EN ISO 24343-1	≤ 0,08 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Thermal resistance	EN ISO 10456	0,03 m ² K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Slip resistance	DIN 51130 / EN 13893	R9 / $\mu \geq 0,30$
Electrical properties	EN 1815 / EN 1081	<2 kV on concrete / > 10 ⁹ Ohm
Underfloor heating		Suitable - max. 27 °C

ENVIRONMENT

TVOC 28 days AgBB test		≤ 100µg/m ³
Recyclable		100%
Plasticizer		Phthalate-free technology



EN ISO 10874
Starfloor Click 20



THE ULTIMATE
FLOORING EXPERIENCE